




GENERAL PURPOSE TRANSFORMER 252L E50394

GUELPH, ONT. BARABOO, WI COMPTON, CA MONTERREY, MX

HPS FORTRESS™
COMMERCIAL POTTED DISTRIBUTION TRANSFORMER

HV/HT	190--240X380--480			Cust. Ref. Réf. du client	
BIL	-			Serial No. No. de série	
TERM. BORNES	H1 H2			Part No. No. de pièce	C1F005XES
	Phase	1			
	kVA	5			
	TYPE	Q			
	Cooling Refroidissement	ANC			
	Temp. Class Classe de Temp.	180 °C			
	Frequency Fréquence	50/60Hz			
	Impédance % @ 135 °C	4.2			
	Encl. Type Type de boîtier	3R			
	Wt Poids	lbs	120		
LV/BT	120/240V				
BIL	-				
TERM. BORNES	X4 X3 X2 X1				

COMPLIES WITH EN61558-2-1 2021-04



ELECTROSTATIC SHIELD
COMPLIES WITH EN60742(1997-06)
DEGREE OF PROTECTION:IP33
THE PRIMARY VOLTAGE RATIO OF 240V OR 480V
IS AVAILABLE AT 60 HZ ONLY WITH A SECONDARY
VOLTAGE OF APPROXIMATELY 130/262V

400001344-8




TITLE:		1PH DISTRIBUTION TRANSFORMER NAMEPLATE INFORMATION		
3	21/07/13	PP	EDB UPDATE	DES: LCEN
2	13/10/30	LC	CHANGED 24V/11A TO 21A	DATE: 08/10/16
NO.	DATE	BY	REVISION	SCALE: NTS


SHEET 1 OF 2
EDBC1F005XES

THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.
3.0 httpd 2026/04/04 02:57

FRONT VIEW



SIDE VIEW



FRONT & BOTTOM PANEL IS HINGED FOR ACCESS TO TERMINALS, BOTTOM MOUNTING HOLES AND REAR KNOCKOUT.

All Dimensions in inches

ENCLOSURE COLOR : ANSI 61 GREY – OUTDOOR

CUSTOMER NOTES:

- HV1 TERMINATED AT BOTTOM REAR
- LV1 TERMINATED AT BOTTOM FRONT

THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.



TITLE: 1PH DISTRIBUTION TRANSFORMER

3	21/07/13	PP	EDB UPDATE	DES: LCEN
2	13/10/30	LC	CHANGED 24V/11A TO 21A	DATE: 08/10/16
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 2 OF 2

EDBC1F005XES