



GENERAL PURPOSE TRANSFORMER 252L E50394

GUELPH, ONT. BARABOO, WI COMPTON, CA MONTERREY, MX

COMMERCIAL POTTED DISTRIBUTION TRANSFORMER

HV/HT	120/208/240/277V			Cust. Ref.	
BIL	-			Réf. du client	
TERM. BORNES	H1 H2 H3 H4 H5			Serial No. No. de série	
				Part No. No. de pièce	C1FC75WES
				Phase	1
				kVA	0.75
				TYPE	Q
				Cooling Refroidissement	ANC
				Temp. Class. Classe de temp.	130 °C
				Frequency Fréquence	60 Hz
				Impédance % @ °C	
LV/BT	120/240V 6.2/3.1A			Encl. Type Type de boîtier	3R
BIL	-			Wt Poids lbs/kg	32.5/14.8
TERM. BORNES	X4 X2 X3 X1				

VOLTS	CURRENT COURANT	% RATED VOLTAGE % TENSION NOMINALE	CONNECTION EACH PHASE CONNECTION PAR PHASE
120	6.5		H1-H2
208	3.8		H1-H3
240	3.3		H1-H4
277	2.8		H1-H5

1-UL-4151-0000P




TITLE: 1 PHASE ENCAPSULATED TRANSFORMER  
NAMEPLATE INFORMATION

3	26/05/20	LC	CHANGED NPL VER:	DES: LCEN
2	26/03/26	LC	CHANGED NPL VER:	DATE: 08/11/24
NO.	DATE	BY	REVISION	SCALE: NTS


SHEET 1 OF 2

EDBC1FC75WES

FRONT VIEW



SIDE VIEW



FRONT & BOTTOM PANEL IS HINGED FOR ACCESS TO TERMINALS, BOTTOM MOUNTING HOLES AND REAR KNOCKOUT.

All Dimensions in inches

ENCLOSURE COLOR : ANSI 61 GREY – OUTDOOR

CUSTOMER NOTES:

- HV TERMINATED AT #14 AWG LEAD WIRE
- LV TERMINATED AT #14 AWG LEAD WIRE



TITLE: 1 PHASE ENCAPSULATED TRANSFORMER

3	26/05/20	LC	CHANGED NPL VER:	DES: LCEN
2	26/03/26	LC	CHANGED NPL VER:	DATE: 08/11/24
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 2 OF 2

EDBC1FC75WES