





FRONT VIEW




SIDE VIEW



BOTTOM VIEW



TERMINAL DETAIL



MTG SLOT DETAIL

hammond POWER SOLUTIONS	TOLERANCES MOUNTING CENTERS = +/– .06" MOUNTING HOLE SIZE = +/– .005"	THIS DRAWING CONTAINS PROPRIETARY INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS INC., AND IS NOT FOR GENERAL DISTRIBUTION	All Dimensions in Inches mm in Parenthesis	REACTOR

hammond POWER SOLUTIONS

HPS CENTURION R
3PH DRY TYPE
REACTOR

MADE IN CANADA

P/N CRX0114CC

INDUCT. 0.143 mH Hz 50/60 AMPS 114 IP00

LR3902

f003776ae

0.6 kV CLASS TEMP CLASS 220°C TYPE JR–2

IND. CONT. EQ. E61431 LISTED

WEIGHT 33/15 (LBS/KG) AMBIENT: 50°C

USE WITH SUITABLY RATED LISTED (ZMVV) LUGS

WINDING TERMINAL TEMPERATURE: 75° C

NOTES:

THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.

hammond POWER SOLUTIONS

TITLE: CENTURION LINE REACTOR

NO.	DATE	BY	REVISION	
				DES: PBAKER
				DATE: 14/07/03
				SCALE: NTS

SHEET 1 OF 1

EDBCRX0114CC

0.0 httpd 2026/11/04 04:55