





FRONT VIEW




SIDE VIEW



BOTTOM VIEW



TERMINAL DETAIL



MTG SLOT DETAIL

hammond POWER SOLUTIONS	TOLERANCES MOUNTING CENTERS = +/- .06" MOUNTING HOLE SIZE = +/- .005"	THIS DRAWING CONTAINS PROPRIETARY INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS INC., AND IS NOT FOR GENERAL DISTRIBUTION	All Dimensions in Inches mm in Parenthesis	REACTOR

hammond POWER SOLUTIONS

HPS CENTURION R
3PH DRY TYPE
REACTOR

MADE IN CANADA

P/N CRX0147PC

INDUCT.0.242 mH Hz 50/60 AMPS 156 IP00

LR3902

0.6 kV CLASS TEMP CLASS 220°C TYPE JR-3

IND. CONT. EQ. E61431 LISTED

WEIGHT 52/24 (LBS/KG) AMBIENT: 50°C

USE WITH SUITABLY RATED LISTED (ZMVV) LUGS

WINDING TERMINAL TEMPERATURE: 75° C

f003776ae

NOTES:

THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.

0.0 httpd 2026/11/05 01:16

hammond POWER SOLUTIONS

TITLE: IRON CORE LINE REACTOR

NO.	DATE	BY	REVISION	DES: PBAKER DATE: 21/12/03 SCALE: NTS

SHEET 1 OF 1

EDBCRX0147PC