




TOP VIEW




FRONT VIEW




SIDE VIEW



BOTTOM VIEW



TERMINAL DETAIL



MTG SLOT DETAIL

hammond POWER SOLUTIONS	TOLERANCES MOUNTING CENTERS = +/- .06" MOUNTING HOLE SIZE = +/- .005"	THIS DRAWING CONTAINS PROPRIETARY INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS INC., AND IS NOT FOR GENERAL DISTRIBUTION	All Dimensions in Inches mm in Parenthesis	REACTOR

hammond POWER SOLUTIONS

HPS CENTURION R 3PH DRY TYPE REACTOR

P/N CRX0183NC

INDUCT. 0.126 MH 50/60 HZ 183 AMPS

0.6 KV CLASS WT: 53/25 lbs/kg IP00

AMBIENT: 50° TEMP CLASS: 220 TYPE JR-3

USE WITH SUITABLY RATED LISTED (ZMVV) LUGS

WINDING TERMINAL TEMPERATURE: 75° C

f003782e

CE

SA® LR3902

UL® LISTED IND. CONT. EQ. E61431

MADE IN CANADA

NOTES:

hammond POWER SOLUTIONS	TITLE: IRON CORE LINE REACTOR				
				DES: PBAKER	SHEET 1 OF 1
				DATE: 24/05/02	EDBCRX0183NC
NO.	DATE	BY	REVISION	SCALE: NTS	

THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.

0.2 httpd 2026/11/05 03:08