



	<p>TOLERANCES MOUNTING CENTERS = <math>\pm .06"</math> MOUNTING HOLE SIZE = <math>\pm .005"</math></p>	<p>THIS DRAWING CONTAINS PROPRIETARY INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS INC., AND IS NOT FOR GENERAL DISTRIBUTION</p>	<p>All Dimensions in Inches mm in Parenthesis</p>	<p>REACTOR</p>
--	--	---	---	----------------

**hammond**

POWER SOLUTIONS

HPS CENTURION R  
3PH DRY TYPE  
REACTOR

P/N CRX0515BC

INDUCT. 0.076 MH 50/60 HZ 515 AMPS

0.6 KV CLASS WT: 220/100 lbs/kg IP00

AMBIENT: 50° TEMP CLASS: 220 TYPE JR-2

USE WITH SUITABLY RATED LISTED (ZMVV) LUGS

WINDING TERMINAL TEMPERATURE: 75° C



MADE IN CANADA

IND. CONT. EQ. E61431

f003782e

NOTES:

**hammond**

POWER SOLUTIONS

TITLE: PROTOTYPE REACTOR

NO.	DATE	BY	REVISION	DES: PBAKER
				DATE: 14/07/04
				SCALE: NTS

SHEET 1 OF 1

EDBCRX0515BC

0.0 wen 2023/08/17 19:39