




TITLE: 3 PHASE LINE REACTOR
NAMEPLATE INFORMATION

NO.	DATE	BY	REVISION	DES:	DATE:	SCALE:
				ASETH	14/08/08	NTS

SHEET 1 OF 2

EDBCRX06D6AE






hammond
POWER SOLUTIONS

INDUCT. 1.5 MH 50/60 HZ
0.6 KV CLASS WT: 7.5 lbs
AMBIENT: 50° TEMP CLASS: 130
TERMINAL TORQUE: 5 LB-IN

HPS CENTURION R
3PH DRY TYPE
REACTOR

P/N CRX06D6AE
6.6 AMPS
ENCL. TYPE 1/IP20
TYPE JR-1A

MADE IN CANADA
f003783e

IND. CONT. EQ. E61431
LISTED



All Dimensions in inches

ENCLOSURE COLOR :ASA 61 GREY

IN/OUT TERMINAL DETAIL

SUITABLE FOR #18-14 CU/AL
CONDUCTORS
1 CONDUCTOR PER PHASE

CUSTOMER NOTES:
- IN/OUT TERMINATED AT TOP



TITLE: 3 PHASE LINE REACTOR
MECHANICAL INFORMATION

				DES: ASETH
				DATE: 14/08/08
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 2 OF 2

EDBCRX06D6AE

0.0 httpd 2026/06/03 15:55

THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.