


THIS DRAWING CONTAINS STRICKLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.



	<p>TOLERANCES MOUNTING CENTERS = +/- .06" MOUNTING HOLE SIZE = +/- .005"</p>	<p>THIS DRAWING CONTAINS PROPRIETARY INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS INC., AND IS NOT FOR GENERAL DISTRIBUTION</p>	<p>All Dimensions in Inches mm in Parenthesis</p>	<p>REACTOR</p>
--	--	---	---	----------------

**hammond**  
POWER SOLUTIONS

HPS CENTURION R  
3PH DRY TYPE  
REACTOR

P/N CRX0700EC

INDUCT. .066 MH 50/60 HZ 700 AMPS

0.6 KV CLASS WT: 246 lbs IP00

AMBIENT: 50° TEMP CLASS: 220 TYPE JR

USE WITH SUITABLY RATED LISTED (ZMVV) LUGS

WINDING TERMINAL TEMPERATURE: 75° C

MADE IN CANADA  
 IND. CONT. EQ. E61431  
 LISTED

f003782e

NOTES:

**hammond**  
POWER SOLUTIONS

TITLE: IRON CORE LINE REACTOR				
DES: AYU				
DATE: 15/03/25				
SCALE: NTS				
NO.	DATE	BY	REVISION	

SHEET 1 OF 1  
EDBCRX0700EC