



- IMPEDANCE SHOWN IS CALCULATED VALUE - NOT GUARANTEED

d000590hb



hammond
POWER SOLUTIONS


Distribution Transformer
Transformateur de Distribution



LR 3902
DISTRIBUTION TRANSFORMER
E147879 ALSO VERIFIED IN ACCORDANCE TO ENERGY STANDARD CB02.2-12

Hyderabad, IN Guelph, ONT Baraboo, WI Monterrey, MX Part No. MG2L0333SESCHC0

Cust. Ref. Ref. du Client	Serial No. No. de Serie	HV/HT	4160V	VOLTS	CONNECTION FOR CONNECTION PAR PHASE	1 2 3 4 5
Phase	1	BIL	30 kV	CURRENT COURANT	% RATED VOLTAGE % NOMINALE	76.3 78.1 80.0 82.1 84.3
Type	F	Term Bornes	H1 H2			105 102.5 100 97.5 95
Cooling Refroidissement	ANN	LV/BT	120/240V			120V LINK X4-X2 & X3-X1 240V LINK X2-X3
kVA	333	BIL	10 kV			
Temp. Rise Echauffement	150 °C	Term Bornes	X4 X2 X3 X1			
Temp Class Classe Temp	220 °C	Energy Regulations Reglements Energetique	DOE 10 CFR PART 431:2016			
Winding Enroulement	CU	Frequency Hz	60			
Impedance % @ 170 °C	5.5	Impedance % @ 170 °C	5.5			
End. Type/Category Type ou categorie de boitier	3R C	Weight Poids	2050			





TITLE: 1PH DISTRIBUTION TRANSFORMER NAMEPLATE INFORMATION			
1	21/07/16	PP	EDB UPDATE
NO.	DATE	BY	REVISION
			DES: DCORTEZ DATE: 17/02/20 SCALE: NTS

SHEET 1 OF 1
EDB MG2L0333SESCHC0
1.0 httpd 2026/04/02 21:57

THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.