



* TOLERANCES STD. +/- 0.1 INCHES [+/- 3 MM]
 * ALL DIMENSIONS IN INCHES [MM]

* SECONDARY FUSE CLIPS ARE SUPPLIED LOOSE WITH TRANSFORMER
 * PRIMARY FUSE CLIPS ARE OPTIONAL
 * PRIMARY AND SECONDARY FINGER GUARD ARE OPTIONAL

hammond
POWER SOLUTIONS

750 VA
50/60 Hz
80 °C RISE

CE

np1390-1c

MADE IN CHINA

CUST. REF. PATENT PENDING

| | | | | |
|------|---|---|---|---|
| 575V | ● | 6 | ● | 1 |
| 460V | ● | 4 | ● | 3 |
| 230V | ● | 3 | ● | 4 |
| 0V | ● | 2 | ● | 5 |
| | ● | 1 | ● | 6 |
| | ● | 6 | ● | 1 |
| | ● | 5 | ● | 2 |
| | ● | 4 | ● | 3 |
| | ● | 3 | ● | 4 |
| | ● | 2 | ● | 5 |
| | ● | 1 | ● | 6 |

CAT. NO. PH750MBMH
 LISTED 252L E50394
 130-6

INDUSTRIAL CONTROL TRANSFORMER

NOTES:

THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.



| | | | | |
|--------------------------------------|----------|----|------------------|------------|
| TITLE: IMPERATOR CONTROL TRANSFORMER | | | | |
| 1 | 21/03/31 | LC | CHANGED NPL VER: | DES: WWONG |
| NO. | DATE | BY | REVISION | SCALE: NTS |

SHEET 1 OF 1
 EDPH750MBMH