



* TOLERANCES STD. + /- 0.1 INCHES[+/- 3 MM]
 * ALL DIMENSIONS IN INCHES[MM]

* SECONDARY FUSE CLIPS ARE SUPPLIED LOOSE WITH TRANSFORMER
 * PRIMARY FUSE CLIPS ARE OPTIONAL
 * PRIMARY AND SECONDARY FINGER GUARD ARE OPTIONAL

INDUSTRIAL CONTROL TRANSFORMER		<p>HV</p> <p>240V 480V</p> <p>1 2 3 4 1 2 3 4</p> <p>4 3 2 1 4 3 2 1</p> <p>12V 24V</p> <p>LV</p>	<p>CAT.NO. PH75QR</p> <p>H1 H3 H2 H4</p> <p>X4 X2 X3 X1</p> <p>CUST. REF. PH75QR</p>		<p>LISTED 252L E50394 130-6 PATENT PENDING</p>
	<p>np1391-1ac</p> <p>75 VA 50/60 Hz 55 °C RISE</p> <p>MADE IN CHINA</p>				

NOTES:



TITLE: IMPERATOR CONTROL TRANSFORMER

NO.	DATE	BY	REVISION	DES:	WWONG	DATE:	07/05/29	SCALE:	NTS

SHEET 1 OF 1

PH75QR

THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.

0.3 httpd 2026/05/10 11:07