



® LR 3902


UL DRY TYPE TRANSFORMER 774J5 E112313

LISTED

GUELPH, ONT. BARABOO, WI COMPTON, CA MONTERREY, MX

THREE PHASE DRY TYPE AUTOTRANSFORMER
AUTOTRANSFORMATEUR SEC TRIPHASE

HV/HT	240Y/139V			Cust. Ref. Réf. du client	
BIL	-			Serial No. No. de série	
TERM. BORNES	H0 H1 H2 H3			Part No. No. de pièce	Y075CECN3LOU
	VOLTS	CURRENT COURANT	% RATED VOLTAGE % TENSION NOMINALE	CONNECTION EACH PHASE CONNEXION PAR PHASE	kVA
	240Y/139V	180.4		H0 H1 H2 H3	75
	216Y/125V 208Y/120V	200.5 208.2		X0 X4 X5 X6 X0 X1 X2 X3	TYPE
LV/BT	208Y/120V		216Y/125V		Cooling Refroidissement
	-		-		ANN
TERM. BORNES	X0 X1 X2 X3 X4 X5 X6				Temp. Rise Echauffement
					130 °C
					Temp. Class Classe de Temp.
					200 °C
					Frequency Fréquence
					60 Hz
					Impédance % @ 150 °C
					.7
					Encl. Type Type de boîtier
					3R
				Wt Poids	lbs
					145
				Winding Enroulement	
					CU



SPACINGS BETWEEN ANY VENTILATED ENCLOSURE PANEL AND ANY ADJACENT WALL SHALL BE A MINIMUM OF 5 INCHES

D003302b



TITLE: 3PH AUTO TRANSFORMER.
NAMEPLATE INFORMATION

2	17/11/28	DC	REVISED DWGS(HCN 67025)	DES: DCORTEZ
1	17/09/11	DC	REVISED DWGS	DATE: 12/10/10
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 1 OF 2

EDB Y075CECN3LOU

2.0 httpd 2026/04/02 01:50

THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.

FRONT VIEW



SIDE VIEW



All Dimensions in inches

ENCLOSURE COLOR : ANSI-61 GREY PAINT OUTDOOR.

HV TERMINAL DETAIL

LV TERMINAL DETAIL

MECHANICAL TYPE LUGS INCLUDED
SUITABLE FOR 350MCM-6 CU/AL
CONDUCTORS
1 CONDUCTOR PER PHASE

MECHANICAL TYPE LUGS INCLUDED
SUITABLE FOR 600MCM-2 CU/AL
CONDUCTORS
1 CONDUCTOR PER PHASE

CUSTOMER NOTES:

- HV TERMINATED AT TOP FRONT
- LV TERMINATED AT BOTTOM FRONT



TITLE: 3PH AUTO TRANSFORMER.

2	17/11/28	DC	REVISED DWGS(HCN 67025)	DES: DCORTEZ
1	17/09/11	DC	REVISED DWGS	DATE: 12/10/10
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 2 OF 2

EDB Y075CFE CN3100