



® LR 3902

UL DRY TYPE TRANSFORMER 77US E112313

LISTED

GUELPH, ONT. BARABOO, WI COMPTON, CA MONTERREY, MX

THREE PHASE DRY TYPE AUTOTRANSFORMER
AUTOTRANSFORMATEUR SEC TRIPHASÉ

HV/HT	600Y/346V (60HZ)	289A
	480Y/277V (50/60HZ)	289A

Cust. Ref. / Réf. du client: _____

BIL: _____

Serial No. / No. de série: _____

TERM. BORNES: H0 H1 H2 H3

Part No. / No. de pièce: Y300PKCH3LOU

VOLTS	CURRENT COURANT	% RATED VOLTAGE % TENSION NOMINALE	CONNECTION EACH PHASE CONNEXION PAR PHASE

kVA: 300

TYPE: K

Cooling / Refroidissement: ANN

Temp. Rise / Echauffement: 150 °C

Temp. Class / Classe de Temp.: 220 °C

Frequency / Fréquence: 60 Hz

Impédance % @ 170 °C: 1.1

LV/BT	480Y/277V (60HZ)	361A
	380Y/219V (50/60HZ)	361A


Encl. Type / Type de boîtier: 3R

BIL: _____

Wt lbs/kg / Poids: 530/241

TERM. BORNES: X0 X1 X2 X3

Winding / Enroulement: CU



D003302b1

SPACINGS BETWEEN ANY VENTILATED ENCLOSURE PANEL AND ANY ADJACENT WALL SHALL BE A MINIMUM OF 5 INCHES EXCEPT WHEN WALL MOUNTED USING HPS WALL MOUNTING KIT

RATED KVA AT 50/60HZ: 240KVA

VOLTAGES SHOWN ARE FOR 3 PHASE, 4 WIRE SYSTEMS. NEUTRAL AND GROUND CONNECTIONS SHOULD BE MADE IN ACCORDANCE WITH LOCAL ELECTRICAL CODE AND STANDARDS REQUIREMENTS



TITLE: 3PH AUTO TRANSFORMER NAMEPLATE INFORMATION

1	15/06/22	RM	HCN: 53368	DES: RBHATIA
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 1 OF 2

EDB Y300PKCH3LOU


THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES. 1.1 http://2026/06/25 01:34




All Dimensions in inches

ENCLOSURE COLOR :ANSI 61 GREY- OUTDOOR

H.V.1. TERMINAL DETAIL



L.V.1. TERMINAL DETAIL



CUSTOMER NOTES:

- HV1 TERMINATED AT TOP FRONT
- LV1 TERMINATED AT BOTTOM FRONT



TITLE:		3PH AUTO TRANSFORMER		
1	15/06/22	RM	HCN: 53368	DES: RBHATIA
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 2 OF 2

EDB Y300PKCH310U